



Fig. 15. Average measured performance.

CONCLUSION

The bandwidths obtained, using the electromechanical configuration just described, are well in excess of 12.4 GHz. This represents an increase in bandwidth of three to four times that previously available. It is safe to assume that this technique will eventually be used to achieve bandwidths in excess of 18 GHz.

ACKNOWLEDGMENT

The author wishes to acknowledge the helpful suggestions of Dr. B. Oliver, Vice President of Research at the Hewlett-Packard Company, and the devoted work of the many individuals at -hp- Associates, who contributed to the development work described here.

REFERENCES

- [1] R. Sugarman, "Sampling oscilloscope for statistically varying pulses," *Rev. Sci. Instr.*, vol. 28, pp. 933-938, November 1957.
- [2] J. M. L. Janssen, "An experimental 'stroboscopic' oscilloscope for frequencies up to about 50 mc/s," *Phillips Tech. Rev.*, vol. 12, pp. 52-58, 1950 and vol. 12, pp. 73-81, September 1950.
- [3] E. Hospitalier, "The slow registration of rapid phenomena by strobographic methods," *The Elec. Engr. (Melbourne, Australia)*, pp. 40-44, January 1, 1904.
- [4] G. B. B. Chaplin "A method of designing transistor avalanche circuits with application to a sensitive transistor oscilloscope," *Digest of Tech. Papers, IRE-AIEE 1958 Transistor and Solid-State Circuits Conf.*, pp. 21-23.
- [5] H. L. Callendar, "An alternating cycle-curve recorder," *The Electrician*, pp. 582-586, August 26, 1898.
- [6] E. W. Golding, *Electrical Measurements and Measuring Instruments*, 3rd ed., revised. London: Pitman and Sons, 1942.
- [7] R. J. D. Reeves, "The recording and Collocation of Waveforms," *Electronic Engrg.*, vol. 31, pp. 130-137, March 1959 and vol. 31, pp. 204-212, April 1959.
- [8] J. G. McQueen, "The monitoring of high-speed waveforms," *Electronic Engrg.*, pp. 436-441, October 1952.
- [9] F. A. Laws, *Electrical Measurements*, 2nd ed. New York: McGraw-Hill, 1938.
- [10] R. Carlson et al., "Sampling oscillography," *IRE WESCON Rec.*, pt. 8, pp. 44-51, 1959.
- [11] R. Carlson, "A versatile new DC-500 MC oscilloscope with high sensitivity and dual channel display," *Hewlett-Packard J.*, vol. 11, nos. 5-7, January/March 1960.
- [12] G. Frye and N. Nahman, "Random sampling oscillography," *IEEE Trans. on Instrumentation and Measurement*, vol. IM-13, pp. 8-13, March 1964.
- [13] C. Yen, "Phase-locked sampling instruments," *IEEE Trans. on Instrumentation and Measurement*, vol. IM-14, pp. 64-68, March/June 1965.
- [14] W. Grove, "A new DC-400 MC sampling 'scope plug-in with signal feed-through capability," *Hewlett-Packard J.*, vol. 15, no. 8, pp. 5-8, April 1964.
- [15] H. Wallman and G. E. Valley, Jr., *Vacuum Tube Amplifiers*. New York: McGraw-Hill, 1948.
- [16] J. Truxal, *Control Systems Synthesis*. New York: McGraw-Hill, 1955, pp. 36-40.
- [17] S. A. Schelkunoff, *Advanced Antenna Theory*. New York: Wiley, 1952.

Theoretical and Practical Applications of Capacitance Matrix Transformations to TEM Network Design

R. J. WENZEL, MEMBER, IEEE

Abstract—TEM propagation on an array of parallel conductors is described in terms of the normalized static capacitance matrix. Important properties of capacitance matrices are discussed and a physical and network interpretation is given to a useful linear transformation of the static capacitance matrix. Several practical applications of capacitance matrix transformations are given. These include

1) equivalent circuits for directional couplers with equal terminations, 2) design procedures for directional couplers with unequal terminations, and 3) element value tables and design details for compact coaxial filter-transformers. Construction details and experimental results are presented for a 3:1 bandwidth filter-transformer constructed with multiple re-entrant coaxial lines.

Manuscript received June 17, 1966; revised August 2, 1966. This work was supported by the U. S. Army Electronics Laboratory, Fort Monmouth, N. J., under Contracts DA 28-043 AMC-00399(E) and DA 28-043 AMC-01869(E).

The author is with The Bendix Corporation, Research Laboratories Division, Southfield, Mich.

I. INTRODUCTION

AN IMPORTANT ASPECT of TEM quarter-wave network synthesis and design is the multiplicity of physical configurations that yield iden-